

CLAIMS:

We claim the following as the subject matter of our invention (hereinafter, "inlet door") as it relates to an improved inlet system for trash chutes, linen chutes, (and any appropriate synonym for either "trash" or "linen" or "chute"), chute shafts and/or chute enclosures, (collectively, and hereinafter "chutes").

1. An inlet door to provide access to a chute constructed as or behind a fire-rated wall whether such wall is existing or new, ~~and if existing, whether or not such an existing wall includes an existing chute frame remaining after the removal of a malfunctioning chute door,~~ that includes several components ~~including wherein its several improvements~~ comprising:

a frame, open in the middle that is configured to function simultaneously in three separate planes: 1) an outward horizontal projected plane (toward the user) of a depth less than four (4") inches ~~in accordance with specific requirements of the Americans' with Disabilities Act (ADA);~~ 2) four flat surfaces interconnected to present a single vertical plane parallel to the wall in which it is to be mounted, set around said middle opening, that presents a vertical surface comprised of the aforementioned flat surfaces of sufficient width to overlap an existing chute door frame in all directions while simultaneously providing a vertical mating plane for the mounting of the inlet door to either a wall surface for new or retrofit construction, or the face of an existing chute frame where the original door has been removed to facilitate retrofit installation of the current art, or to the vertical surface of an adaptor designed as part of the current invention to allow flush mounted installation of the current art in new construction, where said vertical mating surface provides mounting space for fire-stopping expanding gaskets (Stage II Gasketing), when used in conjunction with intumescent caulking to seal any potential internal frame penetrations that could permit the escape of

Header provided for review of this draft only. Please note the following conventions in this draft revision:

Strikethroughs (indicated thusly) indicate REMOVED TEXT.

Underlinings (indicated thusly) indicate ADDED TEXT.

~~smoke, is capable of sealing of hot smoke as defined by National Fire Protection Association~~

~~(NFPA) Standard 105 (NFPA-105); and 3) a third plane, a horizontally projecting planer~~
surface set about the opening and projecting perpendicularly away from the user and the
mounting wall face into the chute throat, such projection accomplished by the judicious
positioning of vertical support elements forming a boundary between the sides of the opening
and the vertical plane of the side mounting surfaces and by the judicious provision of
horizontal projections at right angles to the vertical surfaces of the top and bottom elements
of the frame, to create a four-sided, generally rectangular opening in the middle of the frame
element providing projection into an existing wall opening and/or chute throat thereby
permitting the use of any standard chute opening for disposal through the frame projection
which also serves to establish in a novel manner unique to the current art, both an effective
opening ~~in compliance with the provisions of NFPA 82, Standard on Incinerators and Waste~~
~~and Linen Handling Systems and Equipment, for the prescribed chutes, in addition to~~
~~qualifying as the basis for a new, proposed UL Standard for certification of the present art for~~
and a retrofit installation thereby overcoming the compromising failure of previous art ~~in this~~
regard, and

a stop assembly mounted within said frame providing, cooperatively with the
topmost component of the frame, a mounting surface for gasketing capable of stopping: 1)
the passage of noxious odors emanating from the materials disposed of in the chute and
migrating up the chute surface; and 2) ambient or warm smoke ~~in accordance with the~~
~~definitions of NFPA 105 and the further gasketing requirements of NFPA 80 (Stage I~~
Gasketing), such mounting surface being inclined away from the user at the door bottom to
provide full time gravitational force to properly compress the Stage I gasketing for reliable
performance, and

Header provided for review of this draft only. Please note the following conventions in this draft revision:

Strikethroughs (indicated ~~thusly~~) indicate REMOVED TEXT.

Underlinings (indicated thusly) indicate ADDED TEXT.

a door panel structurally supported by the vertical frame elements creating the sides of the opening by means of a 4" large diameter steel pipe or rod located horizontally and pivotally at the top of the door panel and designed to act in rotation away from the user with the arc of its swing being defined by the locus of points of the bottom of the door panel swinging away from the user, which door panel is comprised of several components divided into two sections of functionality:

an inner door frame comprised a front panel, two side panels and a bottom panel, of heavy gauge metal welded together to form a unitized frame/tray weldment in such a fashion as to utilize the steel pipe or rod at the top of the frame tray as a fifth side of six possible sides, to form a tray for the insertion of fibrous material/insulation for the achievement of the desired ~~Underwriters' Laboratories (UL) B-L~~ labeled construction ~~in accordance with UL Standard 10C (UL-10C), Positive Pressure Fire Tests of Door Assemblies,~~ which provides for control of door deflection and smoke control for such assemblies, and

an outer, two-piece skin of a decorative nature that also provides, cooperatively with holes, one on each side of both the front skin panel and the sides of the interior door frame the receptors for the dual, positive latching mechanism exclusive to the current art, and further, the mounting surfaces for additional Stage II gasketing on the side and bottom surfaces of the door panel, which, in turn, work cooperatively with an additional application of Stage II gasketing on the forward facing side of the installed 4" pipe or rod support at the top to provide full sealing in the event of a hot smoke fire event, and

mechanical, electronic, electro-pneumatic, or fully pneumatic, dual positive latching activation means, novel and unique to the current art, mounted within the inlet door frame designed to engage the door panel and the stop assembly to provide reliable, fail-safe

Header provided for review of this draft only. Please note the following conventions in this draft revision:
Strikethroughs (indicated thusly) indicate REMOVED TEXT.
Underlinings (indicated thusly) indicate ADDED TEXT.

latching means to insure engagement of the Stage I and Stage II gasketing systems as appropriate to both daily usage and fire events, and

supervised access control of the dual, positive latching activation means through the use of a key in the case of the mechanical and fully pneumatic systems, and through the use of magnetic reed switching (in the case of the electronic and electro-pneumatic systems) activated by passing a ~~key-fob-mounted~~ magnet near an opening in the top of the trim that exposes the reed switch which is mounted in the top front face of the frame, activating a timer that both activates the latches and withholds them for a sufficient time, ~~approximately ten seconds~~, to allow a disabled or other individual sufficient disposal time without concern for premature closing if the door panel, and

assisted lifting for the door panel created by the presence of a gas-over-hydraulic-piston, mounted nearly vertically on either side of the frame interior to provide for assisted lift of the door panel insuring that the panel, that can be pushed open by pushing the disposal materials away from the user and, thereby, down the chute, and held open by such disposal for as long as necessary as determined by the time the user requires to dispose of materials as such door panel with assisted lift is held open by the material of disposal, which when fully beyond the open position of the door panel, then allows the door panel to begin to close by gravity, providing for

dampened closing by means of a second gas-over-hydraulic-piston which functions to: first protect the user from debris dropped from above which might impact the door, such dampened closing designed to withstand such impact; and secondly, to control the rate of close to allow the disabled sufficient time to retract their hands safely on top of the fact that the dampened closing allows for minimal pressure, as might be exerted by hands or fingers coming into contact with the closing door panel to stop said door panel ~~in accordance~~

Header provided for review of this draft only. Please note the following conventions in this draft revision:
Strikethroughs (indicated thusly) indicate REMOVED TEXT.
Underlinings (indicated thusly) indicate ADDED TEXT.

~~with the criteria of ADA~~; and thirdly to allow for a pressure increase in the last

approximately two inches of closing travel to insure compression of the Stage I gasketing and to further facilitate the novel and unique dual positive latching of the inlet door, and serving as the basis for a ~~new proposed NFPA standard for a~~ fail-safe, door-closed position in the event of an equipment component malfunction, and

an exterior trim piece, designed variously for retrofit and new construction installation of the inlet door provides: 1) either surface mounted or flush mounted protection to facilitate complete covering of the exterior perimeter of the frame to protect the internal components; and 2) also provides, by virtue of a horizontal projection into the base of the opening, a lip to cover the bottom Stage I gasket to protect it from wear, etc. during normal use, and 3), by provision and placement of opening area perimeter parameters creates additional verification of the criteria for establishing an effective opening ~~as stated in NFPA 82.~~

2. An inlet door according to claim 1 that through a combination of gasketing and caulking ~~with materials in compliance with NFPA 80, NFPA 105, and~~ installed in such a way as to provide air tightness ~~in accordance with UL 1784 provides~~ for added Life Safety to the building, the using public, and to those who protect that public from the dangers inherent in fire events.

Note to Mr. Miller: Following is an Alternate Claim 2, provided in anticipation of the continuation in part (CIP) planned for submittal to USPTO, and, we assume, PCT. The CIP allows an intake door in a chute-building to be directly tied into any manufacturer's Addressable Fire Alarm System installed in accordance with NFPA-72: The National Fire Alarm Code. The CIP would include one additional drawing showing the required device connection and, we assume, additional specification description necessitated by the additional part number reference. As a measure of the significance of this advancement, UL has offered to assist us with petitioning NFPA-72 for inclusion of this technology. We are wondering if that warrants the addition of an additional claim as part of the CIP.

Header provided for review of this draft only. Please note the following conventions in this draft revision:
Strikethroughs (indicated thusly) indicate REMOVED TEXT.
Underlinings (indicated thusly) indicate ADDED TEXT.

Alternate Claim 2. An inlet door according to claim 1 that through a combination of gasketing, caulking and an addressable fire alarm device tie-in provides air tightness and fire alarm system monitoring and alarm for added Life Safety to the building, the using public, and to those who protect that public from the dangers inherent in fire events.

Note to Mr. Miller: Item 3, below, is the original Claim 3, modified per our discussion.

3. An inlet door according to claim 1 that, through a combination of features including a frame, and a calibrated opening in that frame and its associated stop assembly and trim, and various and thoughtful use of fire stopping capabilities creates an inlet door capable of being rapidly installed into a retrofit construction environment while simultaneously improving the Life Safety of both the inhabitants and the facility into which it is introduced.